Technical Data Sheet



PA862 SERIES POWER TAKE-OFF

8 Bolt Single Gear Side Mounted Power Take-Off

The 862 series is a single gear PTO designed for Hino MX06 transmissions with an 8 bolt opening.

Continuing Hydreco Powauto's commitment to maximum torque output, this PTO achieves superior strength with minimum size and is economically priced.

Suits:

Hino MX06 transmissions. (Refer to the eGuide Configurator on www.hydreco.com for confirmation and details)

Product Features

- Output Speed 76.7% of Engine Speed For maximum torque output for pump operation.
- Air Shift Operated For ease of engagement.
- Single Gear Design For simple and smooth operation.
- A Range Of Outputs To allow close coupling or remote mounting of pumps.
- Viton Seals For high temperature conditions.
- Heavy Duty Roller Bearings For higher torque capacity.

POWAUTO

HYDRECO"

HYDRECO HYDRAULIC SOLUTIONS PROVIDER

www.hydreco.com

Technical Data Sheet





PTO DESIGNATION CODES 862 Series



Output Type

08 = 8T Powauto Hydraulic Spline 09 = 14T 12/24 30^o Spline + 35 x 60 Flange Other outputs available on request, subject to MOQ.

Manufacturers Code <

- A = With Pressure Switch
- B = With Mounting Kit
- C = With Mounting Kit & PTO Control Kit

Technical Specific	ations	
Ratings & Service Par	ts	
Torque	Nm / ft.lb	355 / 262
Power @ 500 rpm	kW / hp	18.6 / 24.9
Power @ 1000 rpm	kW / hp	37.2 / 49.8
Output Shaft Rotation		Opposite to Engine
Approximate Bare Mass	kg / lb	
Mounting Kit		MK1208
Mounting Gasket Kit		GK031
Seal Kit		SK117
Bearing Kit		BK117

Note: For full details refer to the owners manual or the eGuide configurator found at www.hydreco.com/markets/ transport

	STRIBUTOR:
1/4 7	oc: PA862—03/1

POWAUTO

DBRAVID BROWN





www.hydreco.com